

NEW PLEX KNOCK MONITOR V3[®]

TURNING TUNING INTO SCIENCE. NEVER MISS KNOCK AGAIN.



Description

The New PLEX Knock Monitor V3 is a fully re-envisioned and vastly improved professional knock detection tool that doubles as a full spectrum CAN BUS datalogger for dyno tuners. The new powerful multi-core processor and dedicated hi-fidelity DSP enable cutting edge knock detection with gain per cylinder, knock signal windowing and engine position signal decoding supporting many OEM trigger patterns. The PKM V3 is housed in a new, much more ergonomic aluminum enclosure that features a high-brightness 2.8" colour TFT IPS display and membrane keypad and comes with an improved M8 industrial wiring and connector system, a 100Mbit Ethernet port and USB datalogging. It is also compatible with the PLEX Device Manager V2 and the PLEX PDA-WIN Data Analysis Software.

Applications

- Knock Detection
- Vibration Analysis
- Generic Datalogging
- Dyno Datalogging
- Engine Tuning

Key Features

- ▶ 2.8" High-brightness IPS TFT display
- ▶ Basic on-device configuration
- ▶ Powerful multi-core processor and new dedicated audio DSP
- ▶ Multi-channel CAN BUS datalogging
- ▶ Real-time data streaming via Ethernet
- ▶ Unlimited USB datalogging
- ▶ Next-level knock detection with gain/cylinder
- ▶ Engine position signal decoding
- ▶ Hi-fi audio recording and playback function

Price Range

1089EUR - 1.399EUR

Technical Specifications

Inputs	
Knock/vibration sensor inputs	2
Analog inputs 0-5V	2 (shared)
Digital inputs 0-5V	2 (shared)
Engine Position/Trigger VR/Hall Inputs	2
Outputs	
Analog outputs 0-5V	2 (shared)
LEDs	4 RGB (configurable)
Communications	
Can Bus Ports	1
Ethernet Streaming/Logging	100Mbit
USB	2 (for config. & logging)
Internal Sensors	
Real Time Clock	with battery backup
Device/Sensor voltage monitor	+12V supp./+5V sensor supply
Device Temperature monitor	Yes
Ambient light sensor	-
Data Channels	
Max Data Channels	Basic 45 / HD 256
Max Flag Channels	Basic 45 / HD 256

ATTENTION - DISCLAIMER

©PLEX TUNING O.E. 2021 | The information contained in these documents is confidential, privileged and only for the information of the intended recipient and may not be used, published or redistributed without the prior written consent of Plex Tuning OE. Additionally, all information in these documents is subject to changes without prior notice.

Technical Specifications - Continued

Data-logging continued	
Memory	USB Flash Dr. or PC logging
Log Rate Max	44kHz knock/vibration, 100Hz other data
Calculations	
Knock Metrics	intensity, count, event, threshold (per cylinder)
Knock Frequency Analysis	real-time
Math Channels	Basic 4 / HD 8
Screen	
Type	RGB TFT IPS
Size	2.8" / 240 x 320 pixels
Brightness	900cd
Refresh rate	50Hz
User Interface	
# of Pages	24
Custom page design	yes
Colour themes	yes
Electrical Data	
Supply Voltage Range	9-30V DC
Current Consumption	max. 2A at 12V
Operating Conditions	
Temperature Range	-20 to +60 degC
Physical	
Connectors	M8 power/CAN M8 knock signals M8 trigger/in-out/5V-sgnd
Dimensions mm	width: 132, height: 76, depth 26
Weight	250g
Material	CNC machined aluminum
Sealing / Ingress Protection	IP5x

PC Software

PLEX Device Manager V2	configuration	free
PLEX PDA-WIN	data analysis	free
PLEX PDA-WIN-PRO	data analysis	paid

Improvements vs previous version (V2)

- Fully re-designed, more ergonomic hardware
- Fully re-designed electronics & new powerful processor
- New and improved connectors and wiring system
- New TFT IPS 2.8" bright colour display
- Significantly improved knock detection accuracy (hi-fi)
- Significantly enhanced knock detection options
- Real-time knock frequency analysis - FFT
- Multi-channel CAN BUS datalogging
- Crank trigger pattern signal decoding
- Knock signal windowing vs engine position
- Per cylinder gain and threshold settings
- Audio recording and playback function

Knock Data & Metrics

- | | |
|----------------------|-------------------------|
| ■ Raw noise | ■ Knock event frequency |
| ■ Raw noise filtered | ■ Knock threshold |
| ■ Knock intensity | ■ Knock count |

Product Versions

- PLEX-KM-V3-Basic (upgradable)
with/without knock sensor set
- PLEX-KM-V3-HD
with or without knock sensor set

Version Comparison

	BASIC	HD
Knock Sensor Inputs	2	2
CAN Bus Port	•	•
Detection per Cylinder	•	•
Knock Threshold	2D	3D
USB Datalogging	•	•
Ethernet	-	•
# of Data Channels	64	256
Engine Position Inputs	for RPM only	•
Gain per Cylinder	-	•
Gain per Sensor	-	•
Knock Windowing	-	•
Real-time FFT	-	•

ATTENTION - DISCLAIMER

©PLEX TUNING O.E. 2021 | The information contained in these documents is confidential, privileged and only for the information of the intended recipient and may not be used, published or redistributed without the prior written consent of Plex Tuning OE. Additionally, all information in these documents is subject to changes without prior notice.

